Description of Measures of Effectiveness

| | | | Portland Area Mainline Alternatives Criteria |
|-------------------------|---|--|--|
| | | Criteria | Description |
| Transportation Measures | Α | Safety Benefits on Maine Turnpike | Using a combination of the engineering standard AASHTO Highway Safety Manual and the USDOT Crash modification factor clearing house, Crash Modification Factors were developed for each alternative. These factors are used to determine the anticipated change in crashes as a result of the proposed alternative and includes physical changes as well as changes in volume. |
| | В | Mainline Turnpike Capacity | Mainline Turnpike Capacity volumes were developed using using the engineering standard USDOT Highway Capacity Manual and calibrated using historical roadway volume information. Each lane is estimated to have a capacity of 1800 vehicles per hour per lane. |
| | С | Change in Mainline Turnpike Demand | The change in mainline turnpike was calculated as discussed in the alternative write-ups. It involves using a variety of information for calculation including the PACTS Travel Demand Model, planned projects, and desired future improvements. Volumes in this category represent the change in vehicles off the road from NB Exit 46-47 during the PM Peak Hour. |
| | D | Mainline Turnpike Volume to Capacity Ratio | Resulting peak demands from Column C are divided by the estimated capacities in Column B to calculation a Volume to Capacity (V/C) ratio. A V/C greater than 1 indicates a road that is over capacity; a V/C between 0.8 and 1.0 indicates a road that is at or nearing capacity; and a V/C less than 0.8 indicates a road that has capacity available. |
| | E | Regional Off- Turnpike Benefits | The PACTS Travel Demand Model provides a total number of miles (by type and location) that are near or at capacity in the region. This estimation was used to determine the effect of each alternative on roadways in the region so that improvement to the Turnpike was not at the detriment to other local roads and arterials. |
| | F | Vehicle Miles Traveled (VMT) | The number of miles traveled during the PM Peak in the PACTS region was totaled for this category, Vehicle Miles Traveled (VMT). An increase in VMT could indicate that users are going out of their way to take a more efficient route or that congestion is increasing and users are traveling a greater length to avoid congested routes; a decrease in VMT could indicate more direct routes are being utilized. |
| | G | Vehicle Hours Traveled (VHT) | The number of hours driven by vehicle during the PM Peak Hour in the PACTS region was totaled for this category, the Vehicle Hours Traveled (VHT). In general, longer VHT times indicate that users are taking a longer time to travel similar routes (i.e. congestion) and shorter times indicate that users are traveling less time. |
| | н | Change in Transit Ridership | PACTS region users opting to take public transit are totaled in this category. The PACTS Travel Demand Model uses pre-determined demographics and proposed improvements to determine the number of public transit trips that will be taken for each alternative. The increased number of riders during the peak hour is shown in this box. |
| | ı | Regional Air Quality | The EPA's Motor Vehicle Emission Simulator (MOVES) was used with local data from MaineDOT to obtain air quality emissions data. EPA's Motor Vehicle Emission Simulator (MOVES) is an industry standard emission modeling system that estimates emissions for mobile sources at the national, county, and project level for criteria air pollutants, greenhouse gases, and air toxics." |
| al Measures | J | Change in Regional Impervious Pavement | The amount of impervious pavement on the roadway was totaled for each alternative and measured in acres. Large increases to impervious pavement can have environmental implications. |
| Environmental Measures | к | Change in Regional Impervious Pavement within Urban Impaired Stream watersheds | The amount of impervious pavement was calculated for each alternative measured in acres within the four watersheds impacted by I-95; Red Brook, Long Creek, Nasons Brook and Capisic Brook. Large increases to impervious pavement within a watershed can have greater environmental implications. |
| | L | Potential Wetland Impacts | Potential wetland impacts were identified for each alternative based on potential future infrastructure improvements or impervious surface expansion. |

DRAFT

| improvement project was calculated de design or construction or is readily available it is green, if it ding identified and the Likely |
|--|
| |
| |
| and are anticipated to grow |
| s been identified or is readily I finally if there is no funding |
| than 1% there is little effect on on, there are several alternatives n toll for these alternatives was also |
| ourdles for implementation. The |
| for instance, land use would require creasing its presence immediately. |
| lementing that alternative. |
| it (converted to transportation ume, increases in capacity, increases |
| d social benefits, it is important that ve Turnpike congestion without |
| |

PAM STUDY PURPOSE

The Maine Turnpike mainline through the Greater Portland area is an essential component of the regional and statewide transportation system. It provides safe and efficient mobility for regional through-traffic, as well as quick and convenient cross-town access to local businesses, municipalities, and other transportation modes.

The purpose of the Portland Area Mainline (PAM) Study is to assess safety and mobility deficiencies on the Maine Turnpike between Scarborough and Falmouth, Maine and, as needed, recommend practicable solutions that preserve and improve long-term highway mobility for the region in a manner that is consistent with the Sensible Transportation Policy Act, enhances the regional transportation system and meets Maine Turnpike Authority responsibilities and reasonable customer expectations.